


# ARDEX X56

## Highly Flexible Tile Adhesive

A highly flexible tile adhesive that is also fast setting. This makes ARDEX X 56 suitable for tiling directly to timber and over heated slabs. **LOW VOC** 



### TILE TYPES

- Ceramic, fully vitrified, porcelain, mosaics, natural stone (excluding moisture sensitive)

### SUBSTRATES

- Cement renders/screeds, concrete, aerated concrete
- Internal timber (particleboard, plywood, mdf, cork) (priming required with ARDEX Optima or ARDEX P 82) with the exception of unbonded timber
- Fibre-cement sheet, plasterboard
- ARDEX undertile liquid applied waterproofing membranes
- Compressed fibre-cement sheet
- Existing ceramic tiles (where glaze is removed)

### LOCATION

- Internal, External (with adequate falls to waste)  
(Not suitable for swimming pools to commercial floors subject to heavy traffic)

### SURFACES

- Floors, Walls

### COLOURS

- Light Grey

### COVERAGE

- Walls: 8m<sup>2</sup> per 15kg
- Floors: 6m<sup>2</sup> per 15kg

### PACKAGING

- 15kg

### CODE

10227



### ARDEX X56 QUICK FACTS

- Fast setting - grout after 4 hours
- Suitable for early age concrete
- Highly flexible



**CONTACT US**  
1300 788 780 | [www.ardexaustralia.com](http://www.ardexaustralia.com)



**Download the Ardex app**  
(search for 'ARDEX Australia')



**SYSTEMARDEX**  
PREMIUM PERFORMANCE