

# Aqua Mix® Stone Deep Clean

## 1 Product Name

Aqua Mix® Stone Deep Clean

## 2 Manufacturer

Custom Building Products  
 Technical Services  
 10400 Pioneer Boulevard, Unit 3  
 Santa Fe Springs, CA 90670  
 Customer Support: 800-272-8786  
 Technical Services: 800-282-8786  
 Fax: 800- 200-7765  
 Email: [contactus@cbpmail.net](mailto:contactus@cbpmail.net)  
[custombuildingproducts.com](http://custombuildingproducts.com)

## 3 Product Description

A concentrated heavy-duty cleaner and degreaser formulated to clean stone surfaces that have been neglected or subjected to heavy use. Aqua Mix® Stone Deep Clean effectively removes dirt, grease and grime, as well as waxes and floor finishes.

### Key Features

- For heavily soiled and neglected areas
- Cleans ground-in dirt, grease, soap scum, and other organic materials
- Strips wax and floor finishes

### Suitable Tile Types

All natural stone (such as granite, limestone, slate, and travertine), ceramic, porcelain, grout, quarry, Saltillo, terra-cotta, cement pavers and masonry surfaces.

### Limitations to the Product

- Do not allow cleaner to come in contact with any non-recommended surface
- Regular use of high alkaline cleaners will reduce sealer life

## 4 Technical Data

### Technical Properties Chart

- Removes common dirt and grease
- Removes acrylic waxes and coatings
- Complies with all federal EPA and SCAQMD standards for VOC

### Technical Chart

| Property | Test Method | Requirement | Typical Results  |
|----------|-------------|-------------|------------------|
|          | pH          | n/a         | 11-12 (alkaline) |

## 5 Instructions

### Application of Product

**USE CHEMICAL-RESISTANT GLOVES, such as nitrile, when handling product.**

Read entire label before using. Sweep, vacuum, or dust surface. Mix Stone Deep Clean as follows:

LIGHT SOIL BUILDUP: Mix 1 part cleaner to 4 parts water.

MODERATE SOIL BUILDUP: Mix 1 part cleaner to 3 parts water.

STRIPPING: Mix 1 part cleaner to 1 part water.



HEAVY SOIL BUILDUP: Use full strength.

Apply solution to surface with mop, sponge, or brush. Allow product to dwell 3 to 5 minutes for cleaning, or 5 to 10 minutes when stripping waxes or finishes. Agitate with synthetic mop, scrub brush, or scrub machine. Do not allow solution to dry on surface. Mop up dirty solution. Rinse thoroughly with clean water.

### Cleaning of equipment

Clean tools with water before material dries.

### Storage

- Close container tightly after each use
- Store in original container only
- Store in and use in temperatures between 45° F to 85° F (7° C to 29° C)
- Store in areas inaccessible to small children
- Do not reuse empty container, wrap and discard in trash or recycle

### Health Precautions

CORROSIVE. CAUSES BURNS. HARMFUL IF SWALLOWED. Wear skin and eye protection. Do not breathe vapor or spray. Contains sodium hydroxide. If in eyes, flush with water for at least 15 minutes. If on skin, wash with soap and water. If respiratory tract is irritated, remove to fresh air. If irritation persists, seek medical attention. If swallowed, DO NOT induce vomiting. Seek medical attention.

## 6 Availability & Cost

| Location | Item Code | Size             | Package |
|----------|-----------|------------------|---------|
| USA      | 030192-4  | 1 qt (946 ml)    | Bottle  |
| USA      | 030193    | 1 gallon (3.8 L) | Bottle  |
| Canada   | C030192-4 | 1 qt (946 ml)    | Bottle  |
| Canada   | C030193   | 1 gallon (3.8 L) | Bottle  |

## 7 Product Warranty

Obtain the applicable **LIMITED PRODUCT WARRANTY** at [www.custombuildingproducts.com/product-warranty](http://www.custombuildingproducts.com/product-warranty) or send a written request to Custom Building Products, Inc., Five Concourse Parkway, Atlanta, GA 30328, USA. Manufactured under the authority of Custom Building Products, Inc. © 2017 Quikrete International, Inc.



# Aqua Mix® Stone Deep Clean

---

## 8 Product Maintenance

Properly applied product requires no special maintenance.

## 9 Technical Services Information

For technical assistance, contact Custom technical services at 800-282-8786 or visit [custombuildingproducts.com](http://custombuildingproducts.com).

## 10 Filing System

Additional product information is available from the manufacturer upon request.

---

### VOC Content

Maximum VOCs: Less than 0.01 grams per liter

### Related Products

Aqua Mix® Sealer's Choice® Gold



# Aqua Mix® Stone Deep Clean

---

## Coverage

| SIZE              | Min Coverage                     | Max Coverage                     |                        |
|-------------------|----------------------------------|----------------------------------|------------------------|
| 1 Gallon (3.78 L) | 150 sq. ft. (15 M <sup>2</sup> ) | 600 sq. ft. (55 M <sup>2</sup> ) | Depending on dilution. |

