


# UNDERTILE PU ACRYLIC HYBRID MEMBRANE

## ARDEX WPM155 RAPID

### Modified Polyurethane Waterproofing Membrane

ARDEX WPM 155 Rapid is a water based polyurethane-acrylic waterproofing membrane developed for high performance under-tile waterproofing.

- Fast drying Polyurethane acrylic membrane
- Excellent film build – easy to gauge thickness
- Class III membrane – in accordance with AS4858 requirements
- Green Star – meets the benchmark for VOC credit in the Green Building Council of Australia's Rating Tools

**LOW VOC** 

#### TYPICAL APPLICATIONS

- Internal and external wet areas, balconies, decks, and other areas that will be tiled or otherwise protected by regular foot traffic.

#### SUBSTRATES

- Concrete, renders and screeds, fibre cement\*, plasterboard\*, plywood\*.
- \*Not recommended for external applications.

#### COVERAGE

- Walls: 17.2m<sup>2</sup> (2 coats) D.F.T. – 0.5mm
- Floors: 17.2m<sup>2</sup> (2 coats) with ARDEX STB Tape – D.F.T. – 0.5mm
- Floors: 8.6m<sup>2</sup> (2 coats) D.F.T. – 1.0mm

#### COLOURS

- Grey

#### DRYING TIMES

- Recoat time: 1–2 hours
- Ready to tile: 4–6 hours
- Full cure: 3 days

#### VOC CONTENT

- 42g/L



#### ARDEX WPM155 RAPID QUICK FACTS

- Tile in 4 hours
- Ardex STB Tape and Liquid Membrane
- Modified polyurethane acrylic waterproof membrane
- Excellent adhesion with ARDEX tile adhesives
- Extended coverage for minimising cost
- Environmentally friendly – solvent free, suitable for confined areas
- Class III Membrane – as per AS/NZS4858 Wet Area Membranes



CONTACT US  
1300 788 780 | [www.ardexaustralia.com](http://www.ardexaustralia.com)



Download the Ardex app  
(search for 'ARDEX Australia')



**SYSTEMARDEX**  
PREMIUM PERFORMANCE