



# Megalastic

## MULTIPURPOSE CEMENT ADHESIVE

### Description

A multi-purpose additive to upgrade the performance of cement based tile adhesives, grouts, screed and other similar systems. Improves adhesion, flexibility and water resistance but maintains workability, open time and pot life. Suitable for outdoors and full immersion once cured.

### Features

- Multipurpose
- Suitable for immersed applications
- Improves bond strength
- Improves flexibility

### Recommended Use

- Increasing adhesive or grout performance
- Immersed installations
- General purpose additive for cement based systems



### Compatible Systems

#### Upgrade the flexibility, adhesion and water resistance of:

- |  |
|--|
| - Cement based adhesives (Except 2 part systems) |
| - Cement based grouts                            |
| - Cement renders                                 |
| - Cement screeds                                 |
| - Cement slurry coat primer                      |
| - Cement mortars                                 |

# Megalastic



## MIXING

**TILE ADHESIVE ADDITIVE:** Use undiluted as a total water replacement or follow instructions on adhesive packaging.

**TILE GROUT ADDITIVE:** Dilute the Megalastic 1:1 with clean water and use this mixture instead of water.

**SAND/CEMENT SYSTEMS:** (e.g. screed, render render or mortar): May be used undiluted or up to 1 part Megalastic to 3 parts water. On site trials may be needed to determine best ratio. Bond to substrate will be improved by treatment with Bostik Multiprime or a slurry coat primer.

**SLURRY COAT PRIMER:** Mix with approximately equal parts fresh cement (or tile adhesive) and keep agitated. Apply slurry to the surface with a brush as a thin coat. Allow to become touch dry and cover within 72 hours. Cover with polymer modified tile adhesive or Megalastic modified screed.

Do not use Megalastic by itself as a primer.

## PRODUCT DETAILS

ITEM NO	ITEM NAME	COLOUR	SIZE
30804113	MEGALASTIC	WHITE	20L

**IMPORTANT NOTES:** This Sell Sheet is not intended as a replacement for the appropriate Technical Data Sheet. Always check the Packaging, Technical Data Sheet and MSDS before using. If there is any doubt contact Bostik before commencing work.

### BOSTIK HOTLINE

**Smart help**  
**1300 267 845**

### BOSTIK AUSTRALIA

Level 1, 6 English Street,  
Essendon Fields, VIC 3041

[www.bostik.com.au](http://www.bostik.com.au)



This document supersedes all previously published literature.

April 2019



**V.O.C  
COMPLIANT**