

Safety Data Sheet

KERAPOXY ADHESIVE comp. A

Safety Data Sheet dated: 4/18/2019 - version 1

Date of first edition: 4/18/2019



1. Identification

GHS Product identifier

Mixture identification:

Trade name: KERAPOXY ADHESIVE comp. A

Trade code: 9025112

Recommended use of the chemical and restrictions on use

Recommended use: Acid-resistant epoxy grout and adhesive for ceramic tiles

Uses advised against: Data not available

Supplier's details

Company: MAPEI AUSTRALIA Pty Ltd

180 Viking Drive Wacol QLD 4076 Australia

Emergency phone number

Australian Poisons Information Centre 24 Hour Service 13 11 26

Police or Fire Brigade 000

2. Hazard identification



Classification of the Hazardous chemical

Skin Irrit. 2	Causes skin irritation.
Eye Irrit. 2A	Causes serious eye irritation.
Skin Sens. 1A	May cause an allergic skin reaction.
Aquatic Chronic 3	Harmful to aquatic life with long lasting effects.

Adverse physicochemical, human health and environmental effects:
No other hazards

GHS label elements, including precautionary statements

Pictograms and Signal Words



Warning

Hazard statements:

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements:

P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P264	Wash hands thoroughly after handling.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352	IF ON SKIN: Wash with plenty of soap and water.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P321	Specific treatment (see supplementary instructions on this label).
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P362	Take off contaminated clothing and wash before reuse.
P501	Dispose of contents/container in accordance with applicable regulations.

Other hazards which do not result in a classification

Other Hazards: No other hazards

The below mentioned crystalline silica, that originally is in the shape of inhalable powder with specific exposure limits, after its mixture into the preparation doesn't involve any exposure risk.

3. Composition/information on ingredients

Substances

no data available

Mixtures

Hazardous components within the meaning of the "Australian Work Health and Safety (WHS)" regulation and related classification:

Concentration (% w/w)	Name	Ident. Numb.	Classification	Registration Number
≥10 - <20 %	reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)	CAS:25068-38-6 EC:500-033-5 Index:603-074-00-8	Eye Irrit. 2A, H319; Skin Irrit. 2, H315; Skin Sens. 1, H317; Aquatic Chronic 2, H411	01-2119456619-26-xxxx
≥2.5 - <5 %	bisphenol F - epoxy resin	CAS:9003-36-5 EC:500-006-8	Skin Irrit. 2, H315; Skin Sens. 1A, H317; Aquatic Chronic 2, H411	01-2119454392-40-XXXX
≥2.5 - <5 %	benzyl alcohol	CAS:100-51-6 EC:202-859-9 Index:603-057-00-5	Acute Tox. 4, H332; Acute Tox. 4, H302; Eye Irrit. 2A, H319	01-2119492630-38-XXXX
≥2.5 - <5 %	oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	CAS:68609-97-2 EC:271-846-8 Index:603-103-00-4	Skin Irrit. 2, H315; Skin Sens. 1, H317	01-2119485289-22-XXXX

4. First-aid measures

Description of necessary first-aid measures

In case of skin contact:

- Immediately take off all contaminated clothing.
- Remove contaminated clothing immediately and dispose of safely.
- After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

- After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.
- Protect uninjured eye.

In case of Ingestion:

- Do not induce vomiting, get medical attention showing the SDS and the hazard label.

In case of Inhalation:

- Remove casualty to fresh air and keep warm and at rest.

Symptoms caused by exposure

- Eye irritation
- Eye damages
- Skin Irritation
- Erythema

Medical attention and special treatment

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

5. Fire-fighting measures

Suitable extinguishing media

- None in particular.
- Water.
- Carbon dioxide (CO₂).

Specific hazards arising from the chemical

- Do not inhale explosion and combustion gases.
- Burning produces heavy smoke.
- Hazardous combustion products: no data available
- Explosive properties: ==
- Oxidizing properties: no data available

Special protective equipment and precautions for fire-fighters

Use suitable breathing apparatus.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Move undamaged containers from immediate hazard area if it can be done safely.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.
Remove persons to safety.
See protective measures under point 7 and 8.

Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.
Retain contaminated washing water and dispose it.
In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.
Suitable material for taking up: absorbing material, organic, sand

Methods and material for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand
Wash with plenty of water.

7. Handling and storage

Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.
Don't use empty container before they have been cleaned.
Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.
Contaminated clothing should be changed before entering eating areas.
Do not eat or drink while working.
See also section 8 for recommended protective equipment.

Conditions for safe storage, including any incompatibilities

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

8. Exposure controls/personal protection

Control parameters – exposure standards, biological monitoring

Predicted No Effect Concentration (PNEC) values

Component	CAS-No.	PNEC Limit	Exposure Route	Exposure Frequency Remark
reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight <= 700)	25068-38-6	0,006 mg/l	Fresh Water	
		0,0006 mg/l	Marine water	
		0,0627 mg/kg	Freshwater sediments	
bisphenol F - epoxy resin	9003-36-5	0,00627 mg/kg	Marine water sediments	
		10 mg/l	Microorganisms in sewage treatments	
		0,003 mg/l	Fresh Water	
		0,294 mg/kg	Freshwater sediments	
		0,0003 mg/l	Marine water	
		0,0294 mg/kg	Marine water sediments	
		0,237 mg/kg	Soil	

benzyl alcohol	100-51-6	1 mg/l	Fresh Water
		0,1 mg/l	Marine water
		5,27 mg/kg	Freshwater sediments
		0,527 mg/kg	Marine water sediments
		39 mg/l	Microorganisms in sewage treatments
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	68609-97-2	0,45 mg/kg	Soil
		2,3 mg/l	Intermittent release
		0,00072 mg/l	Marine water
		0,0072 mg/l	Fresh Water
		66,77 mg/kg	Freshwater sediments
		6,677 mg/kg	Marine water sediments
		80,12 mg/kg	Soil
10 mg/l	Microorganisms in sewage treatments		

Derived No Effect Level. (DNEL)

Component	CAS-No.	Worker Industrial	Worker Professional	Consumer	Exposure Route	Exposure Frequency	Remark	
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700)	25068-38-6	8,3 mg/kg			Human Dermal	Short Term, systemic effects		
		12,25 mg/m3			Human Inhalation	Short Term, systemic effects		
		8,3 mg/kg			Human Dermal	Long Term, systemic effects		
		12,25 mg/m3			Human Inhalation	Long Term, systemic effects		
				3,571 mg/kg		Human Dermal	Short Term, systemic effects	
				0,75 mg/kg		Human Oral	Short Term, systemic effects	
				3,571 mg/kg		Human Dermal	Long Term, systemic effects	
				0,75 mg/kg		Human Oral	Long Term, systemic effects	
benzyl alcohol	100-51-6			20 mg/kg	Human Oral	Short Term, systemic effects		
				4 mg/kg	Human Oral	Long Term, systemic effects		
		110 mg/m3		27 mg/m3	Human Inhalation	Short Term, systemic effects		
		22 mg/m3		5,4 mg/m3	Human Inhalation	Long Term, systemic effects		
		40 mg/kg		20 mg/kg	Human Dermal	Short Term, systemic effects		

8
mg/kg

4
mg/kg

Human Dermal

Long Term, systemic
effects

Appropriate engineering controls

no data available

Individual protection measures, such as personal protective equipment (PPE)

Eye protection:

Use close fitting safety goggles, don't use eye lens.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:

no data available

9. Physical and chemical properties

Color: various

Appearance: paste

Odour: Characteristic

Odour threshold: no data available

pH: no data available

Melting point / freezing point: no data available

Initial boiling point and boiling range: no data available

Flash point: no data available

Evaporation rate: no data available

Flammability (Solid, Gas): no data available

Upper/lower flammability or explosive limits: no data available

Vapour pressure: no data available

Vapour density: no data available

Relative density: no data available

Solubility in water: Insoluble

Solubility in oil: soluble

Partition coefficient (n-octanol/water): no data available

Auto-ignition temperature: no data available

Decomposition temperature: no data available

Viscosity: 2,000,000.00 cPs

Specific heat value: no data available

Saturated vapour concentration: no data available

Release of invisible flammable vapours and gases: no data available

Particle size: no data available

Particle size distribution: no data available

Shape and aspect ratio: no data available

Crystallinity: no data available

Dustiness: no data available

Specific surface area: no data available

Degree of aggregation or agglomeration, and dispersibility: no data available

Biodurability or biopersistence: no data available

Surface coating or chemistry: no data available

VOC (Volatile Organic Compound) : 16.5 (A+B) (Rule 1168) g/l

10. Stability and reactivity

Reactivity

Stable under normal conditions

Chemical stability

no data available

Possibility of hazardous reactions

None.

Conditions to avoid

Stable under normal conditions.

Incompatible materials

None in particular.

SECTION 11: Toxicological information

Information on toxicological effects

Toxicological information of the mixture:

There is no toxicological data available on the mixture. Consider the individual concentration of each component to assess toxicological effects resulting from exposure to the mixture.

Toxicological information on main components of the mixture:

reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight <= 700)	a) acute toxicity	LD50 Oral Rat > 15000 mg/kg
		LD50 Skin Rabbit > 23000 mg/kg
		LD50 Oral Rat = 11400 mg/kg
	i) STOT-repeated exposure	NOAEL Oral Rat = 50 mg/kg
		NOAEL Skin Rat = 100 mg/kg
bisphenol F - epoxy resin	a) acute toxicity	LD50 Oral Rat > 10000 mg/kg
		LD50 Skin Rat > 2000 mg/kg
	i) STOT-repeated exposure	NOAEL Oral = 250 mg/kg
benzyl alcohol	a) acute toxicity	LD50 Skin Rabbit = 2000 mg/kg
		LD50 Oral Rat = 1620 mg/kg
		LC50 Inhalation Rat = 11,00000 mg/l 4h
		LD50 Skin Rabbit = 2 g/kg
		LC50 Inhalation Rat = 8,8 mg/l 4h
		LD50 Oral Rat = 1230 mg/kg
	g) reproductive toxicity	NOAEL Rat = 1072 mg/m3
oxirane, mono[(C12-14- alkyloxy)methyl] derivs.	a) acute toxicity	LD50 Oral Rat > 5000 mg/kg
		LD50 Skin Rabbit > 4500 mg/kg
		LD50 Oral Rat = 17100 mg/kg
		LD50 Skin Rabbit > 3987 mg/kg
		LD50 Oral Rat = 17100 mg/kg

If not differently specified, the information required in the regulation and listed below must be considered as N.A.

- a) acute toxicity
- b) skin corrosion/irritation
- c) serious eye damage/irritation
- d) respiratory or skin sensitisation
- e) germ cell mutagenicity
- f) carcinogenicity
- g) reproductive toxicity
- h) STOT-single exposure
- i) STOT-repeated exposure
- j) aspiration hazard

12. Ecological information

Ecotoxicity

Adopt good working practices, so that the product is not released into the environment.

Eco-Toxicological Information:

Harmful to aquatic life with long lasting effects.

List of components with eco-toxicological properties

Component	Ident. Numb.	Ecotox Infos
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700)	CAS: 25068-38-6 - EINECS: 500-033-5 - INDEX: 603-074-00-8	a) Aquatic acute toxicity : LC50 Fish > 2 mg/L 96 a) Aquatic acute toxicity : EC50 Daphnia > 1,8 mg/L 48 a) Aquatic acute toxicity : LC50 Algae > 11 mg/L 72 a) Aquatic acute toxicity : LC50 Daphnia = 1,3 mg/L 96 b) Aquatic chronic toxicity : NOEC Daphnia = 0,3 mg/L
bisphenol F - epoxy resin	CAS: 9003-36-5 - EINECS: 500-006-8	a) Aquatic acute toxicity : EC50 Fish = 2,54 mg/L 96 a) Aquatic acute toxicity : EC50 Daphnia = 2,55 mg/L 48
benzyl alcohol	CAS: 100-51-6 - EINECS: 202-859-9 - INDEX: 603-057-00-5	a) Aquatic acute toxicity : EC50 Daphnia = 230 mg/L 48 a) Aquatic acute toxicity : LC50 Fish = 770 mg/L 1 a) Aquatic acute toxicity : EC50 Algae = 770 mg/L 72 a) Aquatic acute toxicity : LC50 Fish = 460 mg/L 96 a) Aquatic acute toxicity : EC50 Daphnia = 66 mg/L b) Aquatic chronic toxicity : NOEC Daphnia = 51 mg/L - 21 d a) Aquatic acute toxicity : LC50 Fish Pimephales promelas = 460 mg/L 96h EPA a) Aquatic acute toxicity : LC50 Fish Lepomis macrochirus = 10 mg/L 96h EPA a) Aquatic acute toxicity : EC50 Daphnia water flea = 23 mg/L 48h
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	CAS: 68609-97-2 - EINECS: 271-846-8 - INDEX: 603-103-00-4	a) Aquatic acute toxicity : LC50 Fish > 5000 mg/L 96 a) Aquatic acute toxicity : EC50 Daphnia = 7,2 mg/L 48 a) Aquatic acute toxicity : EC50 Algae = 844 mg/L 72 a) Aquatic acute toxicity : LC50 Fish > 1800 mg/L 96

Persistence and degradability

no data available

Bioaccumulative potential

no data available

Mobility in soil

no data available

Other adverse effects

no data available

13. Disposal considerations

Disposal methods

Recover if possible. In so doing, comply with the local and national regulations currently in force.

14. Transport information

Not classified as dangerous in the meaning of transport regulations.

UN number

no data available

UN proper shipping name

no data available

Transport hazard class(es)

no data available

Packing group, if applicable

no data available

Environmental hazards

no data available

Special precautions for user

no data available

Additional Information

no data available

HazChem Code/Emergency Action code

no data available

15. Regulatory information

Safety, health and environmental regulations specific for the product in question

This Safety Data Sheet has been prepared according to the Australian Work Health and Safety (WHS) act and the Code of Practice on preparation of safety data sheets for Hazardous Chemicals.

AICS: all components are listed

16. Other information

Code	Description
H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This SDS cancels and replaces any preceding release.

Legend to abbreviations and acronyms used in the safety data sheet:

ACGIH: American Conference of Governmental Industrial Hygienists

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

AND: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

ATE: Acute Toxicity Estimate

ATEmix: Acute toxicity Estimate (Mixtures)

BCF: Biological Concentration Factor

BEI: Biological Exposure Index

BOD: Biochemical Oxygen Demand

CAS: Chemical Abstracts Service (division of the American Chemical Society).

CAV: Poison Center

CE: European Community

CLP: Classification, Labeling, Packaging.

CMR: Carcinogenic, Mutagenic and Reprotoxic

COD: Chemical Oxygen Demand

COV: Volatile Organic Compound

CSA: Chemical Safety Assessment

CSR: Chemical Safety Report

DMEL: Derived Minimal Effect Level

DNEL: Derived No Effect Level.

DPD: Dangerous Preparations Directive

DSD: Dangerous Substances Directive

EC50: Half Maximal Effective Concentration

ECHA: European Chemicals Agency

EINECS: European Inventory of Existing Commercial Chemical Substances.
ES: Exposure Scenario
GefStoffVO: Ordinance on Hazardous Substances, Germany.
GHS: Globally Harmonized System of Classification and Labeling of Chemicals.
IARC: International Agency for Research on Cancer
IATA: International Air Transport Association.
IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
IC50: half maximal inhibitory concentration
ICAO: International Civil Aviation Organization.
ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG: International Maritime Code for Dangerous Goods.
INCI: International Nomenclature of Cosmetic Ingredients.
IRCCS: Scientific Institute for Research, Hospitalization and Health Care
KSt: Explosion coefficient.
LC50: Lethal concentration, for 50 percent of test population.
LD50: Lethal dose, for 50 percent of test population.
LDLo: Leathal Dose Low
N.A.: Not Applicable
N/A: Not Applicable
N/D: Not defined/ Not available
NA: Not available
NIOSH: National Institute for Occupational Safety and Health
NOAEL: No Observed Adverse Effect Level
OSHA: Occupational Safety and Health Administration.
PBT: Persistent, Bioaccumulative and Toxic
PGK: Packaging Instruction
PNEC: Predicted No Effect Concentration.
PSG: Passengers
RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.
STEL: Short Term Exposure limit.
STOT: Specific Target Organ Toxicity.
TLV: Threshold Limiting Value.
TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).
vPvB: Very Persistent, Very Bioaccumulative.
WGK: German Water Hazard Class.